

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER POR PATENTS PO Box 1430 Alexandria, Virginia 22313-1450 www.wepto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/594,499	09/28/2006	Kazuo Kuroda	8048-1196	3723
466 YOUNG & TH	7590 11/12/200 IOMPSON	9	EXAM	INER
209 Madison S			SHEN, KEZHEN	
Suite 500 Alexandria, V	22314		ART UNIT	PAPER NUMBER
			2627	
			NOTIFICATION DATE	DELIVERY MODE
			11/12/2000	ET ECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

DocketingDept@young-thompson.com

Application No. Applicant(s) 10/594,499 KURODA ET AL. Office Action Summary Examiner Art Unit 2627 Kezhen Shen -- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

earned patent	term adjustment.	See 37	CFR 1.704(b).

Period fo	or Reply	,
WHIC - Exter after - If NC - Failu Any	CHEVER IS LONGER, FROM THE MAILING DAT nsions of time may be available under the provisions of 37 CFR 1.136(SIX (6) MONTHS from the mailing date of this communication.	 a). In no event, however, may a reply be timely filed apply and will expire SIX (6) MONTHS from the mailing date of this communication. use the application to become ABANDONED (35 U.S.C. § 133).
Status		
2a)⊠	· -	ction is non-final. e except for formal matters, prosecution as to the merits is
Dispositi	ion of Claims	
5)□ 6)⊠ 7)□	Claim(s) 1-3 and 5-12 is/are pending in the applicable of the above claim(s) is/are withdrawn claim(s) is/are allowed. Claim(s) 1-3 and 5-12 is/are rejected. Claim(s) is/are objected to. Claim(s) are subject to restriction and/or expressions.	from consideration.
Applicati	ion Papers	
10)□		
Priority ι	ınder 35 U.S.C. § 119	
a)[Acknowledgment is made of a claim for foreign pr All b) Some * c) None of: Certified copies of the priority documents I Certified copies of the priority documents I Copies of the certified copies of the priority application from the International Bureau (See the attached detailed Office action for a list of	nave been received. nave been received in Application No r documents have been received in this National Stage PCT Rule 17.2(a)).
Attachmen	* *	h
	e of References Cited (PTO-892) e of Draftsperson's Patent Drawing Review (PTO-948)	4) Interview Summary (PTO-413) Paper No(s)/Mail Date

	Motion

Attachment(s)		
Notice of References Cited (PTO-892)	4) Interview Summary (PTO-413)	
Notice of Draftsperson's Patent Drawing Review (PTO-948)	Paper No(s)/Mail Date	
3) Information Disclosure Statement(s) (PTO/S6/08)	5). Notice of Informal Patert Application.	
Paper No(s)/Mail Date	6) Other:	

Page 2

Application/Control Number: 10/594,499

Art Unit: 2627

DETAILED ACTION

Response to Arguments

Applicant's arguments with respect to claims 1-3, 5-12 have been considered but are moot in view of the new ground(s) of rejection.

In regards to the amendments to claims 1, 7 and 12 in view of the 102(b) rejection, applicant argues against the limitation of "wherein the identification information is star/end address information indicating a start or end position of at least one portion of said first buffer area formed in advance. The examiner disagrees with the argument. The management area contains address information indicative of the first buffer area (8b1-8b4 of Drawing 3, [0047] address number is written to LPP) which also teaches the buffer area are prepit which is formed in advanced as the pre-recording area. Further, the star and end address of the buffer area are defined as by the N1-N8 addresses (N1 – N8 of Drawing 3, [0067] – [0083]). Therefore, the rejection in view of Junsaku still stands in view of the amendments.

In regards to the double patenting rejection, applicant argues against the claims US 7,502,285 to not disclose the novel features of claims 1-12. Upon further examination, the examiner has concluded the features claimed in the limitation of the current application are not the features claimed in patent US 7,502,285. Therefore, the double patenting rejection has been withdrawn.

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

Art Unit: 2627

A person shall be entitled to a patent unless -

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claims 1-3 and 5-12 are rejected under 35 U.S.C. 102(b) as being anticipated by Junsaku et al. JP 2002-216361.

Regarding claim 1, Junsaku et al. teach an information recording medium comprising: a first recording layer in which a first recoding track path for recording record information, is formed (3 of Drawing 1, [0034] - [0037], front recording layer); a second recording layer which is disposed on said first recording layer and in which a second recoding track path for recording the record information, is formed in an opposite direction to the first recording track path (2 of Drawing 1, [0034] - [0037], back recording layer); and further, a first buffer area (8b1-8b4 of Drawing 3, [0046], nonrecord section) for preventing a recording or reproduction position from deviating from said first recording layer or said second recording layer ([0046] - [0055]), and for layer jump, on an outer circumferential edge portions of said first recording layer and said second recording layer ([0046] - [0055]), at least one portion of said first buffer area being formed in advance as a pre-recording area, of embossed pits or pits obtained by irradiation of recording laser ([0047], [0056] prepit), and said information recording medium further comprising a management area to record therein identification information indicating whether or not at least one portion of said first buffer area is formed in advance as the pre-recording area ([0046] - [0055], [0066] - [0076] 8b1-8b4 of Drawing 3, [0047] address information), wherein the identification information is start /

Art Unit: 2627

end address information indicating a start or end position of at least one portion of said first buffer area formed in advance (N1-N8 of Drawing 3, 100591).

Regarding claim 2, Junsaku et al. teach the information recording medium according to claim 1, wherein said management area is a recording management area for managing the recording of the record information (Drawing 3, [0046] – [0055], [0066] – [0076]).

Regarding claim 3, Junsaku et al. teach the information recording medium according to claim 1, wherein pre-format address information is recorded in said first recording layer and said second recording layer ([0046] – [0055] non-record section), and identification information indicating that said first buffer area is formed in advance (Abstract, [0047] prepit, prewrite and preemboss), is added to the pre-format address information ([0046] – [0055]).

Regarding claim 5, Junsaku et al. teach the information recording medium according to claim 4, wherein the start/end address information indicates that said first buffer area is not formed in advance, when having a predetermined value ([0046]).

Regarding claim 6, Junsaku et al. teach the information recording medium according to claim 1, wherein (i) at least one portion of said first buffer area is formed in advance of embossed pits ([0046] – [0055]), and a recording film capable of performing additional recording is laminated thereon (f00651).

Regarding claim 7, Junsaku et al. teach an information recording apparatus for recording a first portion of the record information along the first recording track-path (3 of Drawing 3, [0036]), and for recording a second portion of the record information, with

Art Unit: 2627

a recording direction turned around, along the second recording track path (2 of Drawing 3, [0036]), with respect to an information recording medium constructed such that a first recording layer has a first recording capacity and a second recording layer has a second recording capacity ([0034] - [0035] the two recording layers has two different recording area), said information recording medium comprising: a first recording layer in which a first recoding track path for recording record information, is formed (3 of Drawing 1, [0034] - [0037], front recording layer); a second recording layer which is disposed on said first recording layer and in which a second recoding track path for recording the record information, is formed in an opposite direction to the first recording track path (2 of Drawing 1, [0034] - [0037], back recording layer); and further, a first buffer area (8b1-8b4 of Drawing 3, [0046], non-record section) for preventing a recording or reproduction position from deviating from said first recording layer or said second recording layer ([0046] - [0055]), and for layer jump, on an outer circumferential edge portions of said first recording layer and said second recording layer ([0046] -[0055]), at least one portion of said first buffer area being formed in advance as a prerecording area, of embossed pits or pits obtained by irradiation of recording laser ([0047], [0056] prepit), and said information recording medium further comprising a management area to record therein identification information indicating whether or not at least one portion of said first buffer area is formed in advance as the pre-recording area ([0046] - [0055], [0066] - [0076] 8b1-8b4 of Drawing 3, [0047] address information), wherein the identification information is start / end address information indicating a start or end position of at least one portion of said first buffer area formed in

Art Unit: 2627

advance (N1-N8 of Drawing 3, [0059]), said information recording apparatus comprising; a writing device capable of respectively writing the first portion and the second portion into said first recording layer and said second recording layer ([0028] -[0029]), a calculating device for calculating a turn-around address on the first recording track path, in turning around from the first recording track path to the second recording track path ([0028], [0047] - [0055]), in a case where the first portion with an information amount which does not satisfy the first recording capacity, out of the record information. is written along the first recording track path ([0047] - [0055]), and where the second portion with an information amount which does not satisfy the second recording capacity is written along the second recording track path ([0047] - [0055]), on the basis of a total information amount of the record information ([0048] - [0049] from start address to target address), the start/end address information ([0045]), the first recording capacity ([0045] address of beginning and ending record feasible region of the front recording layer), and the second recording capacity ([0045] address of beginning and ending record feasible region of the back recording layer), and a controlling device for controlling said writing device ([0048]), to write the first portion along the first recording track path up to the calculated turn-around address ([0047] - [0055]), to add buffer data so as to form another portion of said first buffer area in said first recording layer and said second recording layer ([0046] the non-record section can be recorded), and to write the second portion along the second recording track path from a correspondence address in said second recording layer corresponding to the calculated turn-around address in said first recording layer ([0047] - [0055]).

Art Unit: 2627

Regarding claim 8, Junsaku et al. teach the information recording apparatus according to claim 7, wherein said controlling device controls said writing device to write the buffer data ([0046] recording non-record section), in order to form a second buffer area for preventing a recording or reproduction position from deviating from an inner circumferential edge portion of said second recording layer (8a-8d of Drawing 3), in response to a finalize instruction for maintaining compatibility with a read-only or reproduce-only information recording medium ([0078] – [0083]).

Regarding claim 9, Junsaku et al. teach the information recording apparatus according to claim 7, wherein said controlling device controls said writing device to write the buffer data ([0046] recording non-record section), in order to form a third buffer area located on an inner circumferential side of said first buffer area (8a-8d of Drawing 3), on the basis of a total information amount of the record information ([0048] – [0049] from start address to target address), the start/end address information ([0045]), the first recording capacity ([0045] address of beginning and ending record feasible region of the front recording layer), and the second recording capacity ([0045] address of beginning and ending record feasible region of the back recording layer).

Regarding claim 10, Junsaku et al. teach the information recording apparatus according to claim 7, wherein said controlling device controls said writing device to write the buffer data ([0046] recording non-record section), in order to form a fourth buffer area linked to said first buffer area (8a-8d of Drawing 3), on the basis of a total information amount of the record information ([0048] – [0049] from start address to target address), the start/end address information ([0045]), the first recording capacity

Art Unit: 2627

([0045] address of beginning and ending record feasible region of the front recording layer), and the second recording capacity ([0045] address of beginning and ending record feasible region of the back recording layer).

Regarding claim 11, Junsaku et al. teach the information recording apparatus according to claim 7, wherein said controlling device controls said writing device to write the buffer data ([0046] recording non-record section), in order to form a plurality of buffer areas located on an inner circumferential side of said first buffer area (8a-8d of Drawing 3), on the basis of a total information amount of the record information ([0048] – [0049] from start address to target address), the start/end address information ([0045]), the first recording capacity ([0045] address of beginning and ending record feasible region of the front recording layer), and the second recording capacity ([0045] address of beginning and ending record feasible region of the back recording layer).

Regarding claim 12, the limitations have been analyzed and rejected with respect to the reasons given above in claim 7. Further, one of ordinary skill in the art would have recognized the need for a method to operate the apparatus as claimed in claim 7.

Conclusion

Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within

Art Unit: 2627

TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Kezhen Shen whose telephone number is (571) 270-1815. The examiner can normally be reached on Monday-Friday 10am-6pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Joseph Feild can be reached on (571) 272-4090. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Art Unit: 2627

Examiner, Art Unit 2627

Supervisory Patent Examiner, Art Unit 2627